

WOOD LOCKERS
SECTION 10 500

PART 1 - GENERAL

1.1 SECTION INCLUDES

- A. Custom wood lockers and accessories.

1.2 REFERENCES

- A. Minimum standard for wood lockers shall conform to AWI (Architectural Woodwork Institute) Architectural Woodwork Quality Standards Illustrated.

1.3 QUALITY ASSURANCE

- A. All parts and hardware shall be AWI compliant, structurally sound and free from defects, in material and workmanship under normal use and service for the full warranty period.

1.4 SUBMITTALS

- A. Product Data: Available upon request, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.
 - 4. Product data specific to materials used in construction of locker.
- B. Shop Drawings: Indicate locker plan layout for All Wood Lockers contracted installations, component profiles and elevations, schedule of finishes, and accessories.

1.5 PRODUCT DELIVERY, STORAGE, AND HANDLING

- A. Store products in a dry, ventilated area until ready for installation.
- B. Protect finishes from moisture, soiling and damage during handling.

1.6 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.
- B. During and after installation, maintain same temperature and humidity conditions in building spaces as will occur after occupancy.
- C. Protect locker finish and adjacent surfaces from damage.

**WOOD LOCKERS
SECTION 10 500**

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: All Wood Lockers ; 1050 W State St. Newcomerstown, OH 43832 ; 740-498-8363 ; info@allwoodlockers.com

2.2 MATERIALS

- A. Locker Frame: Tops, sides, and back shall be constructed of ¾" thermally fused melamine.

1. Expansion / contraction within +/- 1/16" per locker.

- B. Locker Models:

1. Solid Wood Raised Panel Club Locker - One Tier
- a. Height: 76"
 - b. Width: 12" additional widths: 15", 18", 24"
 - c. Depth: 18" additional depths: 20", 21", 24"
 - d. Double Prong Ceiling Hook, matte nickel finish.
 - e. 5" deep wallet shelf
 - f. Full depth footlocker shelf
 - g. 4" high black melamine base with black aluminum corner guards
 - h. Interior Finish: White

- C. Visible Edges: Sealed with half mm black PVC edge banding.

1. Edge banding to match locker finish also available.

- D. Locker Doors:

1. Solid Wood Raised Panel Door
- a. 7-piece design with center rail
 - b. ¾" thick solid wood stiles and rails
 - c. 9/16" thick solid wood center panels
 - d. Species: Red Oak or Maple
 - e. All joints are dominoed and glued

- E. Locker Door finish:

1. Wood surfaces are sealed with a catalyzed conversion varnish (Low VOC).
2. Wood stains use solvent-based stain.

- F. Standard hardware:

1. Number plate, 1-3/4"w x 1"h black tag with 3/4" high contrast digits.
2. Ives Double Prong Ceiling Hook, matte nickel finish.

WOOD LOCKERS
SECTION 10 500

3. Heavy Duty concealed European hinges with 110 degree opening, six-way adjustment -- Four hinges per door.

G. Door Locks:

1. Standard lock: Hafele Hasp Lock, matte nickel finish.
2. Other lock options available: DigiLock, Keyless, MasterLock and more.

- H. Venting: 1/4" openings between door and interior locker cabinet allows continuous air flow.

2.3 FABRICATION

- A. Locker shall be fabricated using doweled and glued & nailed assembly process.
- B. Fabricate lockers square, rigid and without warp, with the finished faces flat and free of scratches and chips.
- C. Machine all parts and attachment holes accurately and without chips.

PART 3 - EXECUTION

2.1 EXAMINATION

- A. Do not begin installation until adjacent substrates and finishes have been properly prepared.
- B. If preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

2.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.
- C. Verify adequacy of backing and support framing.

2.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. If All Wood Lockers is not contracted for installation, client must unload lockers from the delivery truck.
- C. Set and secure lockers in place; rigid, plumb, and level.

**WOOD LOCKERS
SECTION 10 500**

- D. Use concealed joint fasteners to align and secure adjoining cabinet units.
- E. Secure lockers with anchor devices to suit substrate materials.
- F. Install end panels, filler panels, tops and bases as indicated on the approved shop drawings.
- G. Install accessories.

2.4 ADJUSTING

- A. Adjust moving or operating parts to function smoothly and correctly.

2.5 CLEANING

- A. Use a damp cloth or sponge and a mild soap, detergent, or diluted household cleaner. Avoid abrasive cleaners, bleach, and excessive scrubbing. For grease stains, use an ammoniated or vinegar-based glass cleaner. For tougher stains, try a paste of baking soda and water with a soft brush. Rinse thoroughly and dry with a soft, clean cloth. Don't flood the wood or laminate, especially near seams, as water can cause swelling.

2.6 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION 10 500